

Technical Data Ultra ONE® Alcoa® Wheel with MagnaForce® alloy



Wheel size	22.5"x9.00"
Mounting hole Ø	26 mm and 32 mm
Weight 26mm Ø	23.0 kg (vs 23.7 kg for 89252x)
Weight 32 mm Ø	22.9 kg (vs 23.5 kg for 89251x)
Max. load	4250 kg (vs 4125 kg for 8925xx)
Offset	155.5 mm
Half dual space	176 mm
Disc thickness	20.5 mm
Number of mounting holes	10
Mounting hole circle Ø	335 mm
Center bore Ø	281 mm
Dual mounting	yes
Valve	70MS07N2
Balancing weights	clip-on and adhesive on both sides of the rim



Part number/ finish	Mounting hole Ø 26 mm	Mounting hole Ø 32 mm
Brushed	89U520	89U510
LvL ONE®	89U527	89U517
Dura-Bright®	89U523DB	89U513DB
Dura-Flange®	89U520DF	

Available as from Q4, 2019



Arconic Wheel and Transportation Products
E: info.wheels@arconic.com
W: www.alcoawheelseurope.com



Alcoa® Wheels¹ is a product brand of Arconic
© 2019 Arconic Inc. or an Arconic Inc. affiliate.

¹ The Alcoa trademarks are owned by Alcoa USA Corporation and used by Arconic Inc. and its subsidiaries under license from Alcoa USA Corporation.



Technical Data Ultra ONE[®] Alcoa[®] Wheel with MagnaForce[®] alloy



Wheel size	22.5"x8.25"
Mounting hole Ø	26 mm and 32 mm
Weight 26mm Ø	22.2 kg (vs 23.2 kg for 88252x)
Weight 32 mm Ø	22.1 kg (vs 23.1 kg for 88251x)
Max. load	3750 kg
Offset	148.1 mm
Half dual space	167.6 mm
Disc thickness	19.5 mm
Number of mounting holes	10
Mounting hole circle Ø	335 mm
Center bore Ø	281 mm
Dual mounting	yes
Valve	60MS00N
Balancing weights	clip-on and adhesive on both sides of the rim



Part number/ finish	Mounting hole Ø 26 mm	Mounting hole Ø 32 mm
Brushed	88U520	88U510
LvL ONE [®]	88U527	88U517
Dura-Bright [®]	88U523DB	88U513DB
Dura-Flange [®]	88U520DF	88U510DF
Dura-Bright [®] /Dura-Flange [®]	88U523DD	88U513DD

Available as from Q4, 2019



Arconic Wheel and Transportation Products

E: info.wheels@arconic.com

W: www.alcoawheelseurope.com



Alcoa[®] Wheels¹ is a product brand of Arconic

© 2019 Arconic Inc. or an Arconic Inc. affiliate.

¹ The Alcoa trademarks are owned by Alcoa USA Corporation and used by Arconic Inc. and its subsidiaries under license from Alcoa USA Corporation.

